

THE BOND WITHIN
MAKES YOU STRONG

SOLID HAI



CENTURYPLY®
BOND 710

Now With

VIROKILL
Kills 99.99% Viruses

21

TWENTY ONE YEAR
WARRANTY



100% BORER &
TERMITE PROOF



BOILING
WATER PROOF

Bond 710 is a special BWP Marine Grade plywood, developed to be borer and termite proof and meet all the parameters of IS:710.

- Unique GLP formula to make plywood borer and termite proof
- 21-Year Warranty*
- More number of plies for more strength
- Quadra Press Technology for high strength
- Manufactured with surface calibration process for smooth surface finish
- Green Building certified

*Check the Warranty Terms & Conditions



TWENTY ONE YEAR
WARRANTY



TECHNICAL SPECIFICATIONS*

PLYWOOD

Moisture Content (%)	7 - 10
Preservative Treatment	Two Tier Treatment: 1. Glue Line Protection 2. Finished panels are treated with ACC (Acid Copperchrome Compound)
Adhesion of plies	Excellent
Specific Gravity	> 0.68
Water Absorption (%)	< 5
Screw holding strength (Kgf)	> 130
Nail holding strength (Kgf)	> 110
Static Bending Strength (N/mm ²)	
Modulus of rupture (MOR): Along the grain: Across the grain:	> 40 > 55
Modulus of elasticity (MOE): Along the grain: Across the grain:	> 5000 > 6000

BLOCKBOARD

Moisture Content (%)	8 - 12
Modulus of Elasticity (N/mm ²)	> 5500
Modulus of Rupture (N/mm ²)	> 55
Preservative Treatment	Two Tier Treatment: 1. Glue Line Protection 2. Finished panels are treated with ACC (Acid Copperchrome Compound)
Adhesion of plies	Excellent
Specific Gravity	> 0.52
Screw holding strength (Kgf)	> 110
Nail holding strength (Kgf)	> 70
Static Bending Strength (N/mm ²)	
Modulus of rupture (MOR): Along the grain: Across the grain:	> 50
Modulus of elasticity (MOE): Along the grain: Across the grain:	> 5000

*Conditions apply