

LASTING PEACE OF MIND.


CenturyPly Club Prime. India's most trusted plywood.



CENTURYPLY®
CLUB PRIME



**BORER &
TERMITE PROOF**



**BOILING
WATER PROOF**



**SUPERIOR
STRENGTH**



FIREWALL
TECHNOLOGY

Now With
VIROKILL
Kills 99.99% Viruses

Club Prime is a 'Boiling Water Proof' plywood from CenturyPly, made by a special pre-pressing technique that ensures equal distribution of moisture and adhesive. The first in class BWP plywood with fire retardant properties.

- A unique GLP formula is used to make the plywood borer and termite proof
- Boiling Water Proof (IS 710 BWP Grade)
- 30-Year Warranty*
- Multi-pressing technology for enhanced properties
- Only plywood in the industry which passes 25 stringent in-house tests
- 100% fire retardant
- Confirming to ASTM (American society for testing and materials) and conforming to British standard
- Green building certified
- Duplicate proof
- 100% Hard wood
- 100% Composed Core for Gapless Product
- Calibrated

*Check the Warranty Terms & Conditions










CALIBRATED










TECHNICAL SPECIFICATIONS*

PLYWOOD

Moisture Content (%)	 8 - 12
Preservative Treatment	 Two Tier Treatment: 1. Glue Line Protection 2. Finished panels are treated with ACC (Acid Copperchrome Compound)
Adhesion of plies	 Excellent
Specific Gravity	 > 0.69
Screw holding strength (Kgf)	 > 150
Nail holding strength (Kgf)	 > 120
Static Bending Strength (N/mm ²)	
Modulus of rupture (MOR):	
Along the grain:	 > 40
Across the grain:	> 55
Modulus of elasticity (MOE):	
Along the grain:	> 5000
Across the grain:	> 6000

BLOCKBOARD

Moisture Content (%)	 8 - 12
Preservative Treatment	
Adhesion of plies	 Excellent
Specific Gravity	 > 0.54
Screw holding strength (Kgf)	 > 120
Nail holding strength (Kgf)	 > 70
Static Bending Strength (N/mm ²)	
Modulus of rupture (MOR):	
Along the grain:	 > 50
Modulus of elasticity (MOE):	
Along the grain:	> 5000

*Conditions apply